

# RAPID UHS



## SHINY ANTI-SLIP DETERGENT-RENOVATOR FOR SPRAY MAINTENANCE WITH UHS MACHINES

- Anti-slip effect tested by UL laboratories
- Excellent wet glossy effect
- Excellent film regeneration and good cleaning power



Special multi-purpose emulsion that cleans, repairs and polishes metal cross-linked acrylic waxes all in one. Registered with Underwriters Laboratories Inc. as anti-slip, high resistance product.

### HOW TO USE

Damp mop the floor. Spray a small amount of Rapid UHS and then polish using a single disc machine at high speed fitted with a hi-speed disc.



### DILUTION

Ready to use.

### FEATURES

Product yields (m<sup>2</sup>/lt):

Operation category	Conc.%	Product yield (m <sup>2</sup> /lt)	Notes
SPRAY BUFFING	100%	250	Application with high speed single disk machine (1500 rpm)

Volume (lt) of pure product diluted according to suggested dilutions.

## RAPID UHS

### TECHNICAL DATA

**ASPECT:** Opaque liquid

**COLOR:** Blue

**PERFUME:** Lavender

**COV:** 0,10%

PH	Active substance [%]	Density (g/ml)	Pressure (bar)	Viscosity (cP)	Total dry residue [%]
9,0 ± 0,5		1.006			5,7 ± 0,6

### WARNINGS

Harmful to aquatic life with long lasting effects. Avoid release to the environment. Dispose of contents/container in accordance with applicable regulations. Contains ZINC AMMONIA CARBONATE COMPLEX, METHYLCHLOROISOTHIAZOLINONE, METHYLISOTHIAZOLINONE. May produce an allergic reaction.

### NOTES

Do not use Rapid UHS at temperatures below 10° C. Keep away from freezing.  
Before use, please always refer to the Technical Data Sheet and the Safety Data Sheet, with the exposure scenario, of the product. Use the PPE specified in the Safety Data Sheet.  
Sutter Professional cannot be considered liable for any damages due to improper product use.  
**Only for professional use. Safety data sheet available on request.**

### PACKAGING

Code	Size	Quantity	Pallet
3812	Kg 5	4	9x4=36