

BETON



ACRYLIC SEALER FOR CONCRETE AND POROUS FLOORS

- Suitable for porous floors (ex.terracotta floors etc..)
- Anti-dust effect and anti-stain effect
- Resistant to heavy traffic

Acrylic sealer specially designed for very porous floors. Anti-dust effect and resistant to heavy traffic. Excellent anti-stain effect.

HOW TO USE

After carefully removing wax and any saltpetre deposits, apply two coats of sealer using the special wax applicator (the first coat should be diluted with 50% water to make impregnating easier). Leave to dry approximately 45 min. between one coat and the next.

DILUTION

Ready to use.

TECHNICAL DATA

ASPECT: Opaque liquid

COLOR: Creamy white

PERFUME: Technical

PH	Active substance [%]	Density (g/ml)	Pressure (bar)	Viscosity (cP)	Total dry residue [%]
7,7 ± 0,5		1.018			20,5 - 21,5

WARNINGS

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Contents METHYLCHLOROISOTHIAZOLINONE, METHYLISOTHIAZOLINONE: May produce an allergic reaction.

NOTES

Check that the sealer adheres to concrete floors and do not apply BETON at temperatures below 10° C. Keep away from freezing. PRODUCT FOR PROFESSIONAL USE ONLY. SAFETY DATA SHEET AVAILABLE FOR PROFESSIONAL USERS.

BETON

PACKAGING

Code	Size	Quantity	Pallet
3822	kg 5	4	9x4=36